Entry Door Cutters

Application:

For production of solid timber doors both internal and external. Used on spindle moulders or D.E.T machines.

Special Features

Large range of standard profiles. Available in left and right hand rotation. Body supplied in high strength steel to give long lasting tool body with many years of service.

Technical Details:

Steel construction. Balanced design for smooth running. Bores to H7 tolerance. Positive accurate insert location.

Splay Profile

Bullnose Profile





3 + 3 Wing

CROWN TOOLING



Lambs Tongue




Ovolo Profile



Rail Cutter Set:

Tooling set consisting of Rebate and Profile cutters. Profile cutters have backing plates and the ability to interchange profiles in the one cutter set. **Recommended for mechanical feed**.

Wedge 20x30x2 WSEDP2030-BS Wedge Screw M5 x 25SHCS Wedge 20x12x1.5 WSEDP2012-BS Key T15 FLAG End Stop M4x9HD Backing Plate BPSEDP2030-BS Backing Plate Screw M4 x 7 HD Scribe Screw SS-M5x12 Key 4A/F-TEE



D

Sizes Available

CODE	D	В	Width	Insert	Insert
SEDP-1802030-1 ¹ / ₄ or 40	180	1¼ or 40	20	20x30x2 FT	14x14x2
SEDR-1802012-1¼ or 40	180	1¼ or 40	20	20x12x1.5	14x14x2

Last digits on code number denotes bore size choose either $1\!\frac{1}{4}$ or 40.

Tenon Cutter Set:

Tooling set consisting of Rebate and Profile Cutters. Profile cutters have backing plates and the ability to interchange profiles in the one cutter set. **Recommended for mechanical feed.**

Spare Parts:

Wedge Backing Plate Wedge Screw Backing Plate Screw	WSEDP2030-BS BPSEDP2030-BS M5 x 25SHCS	Sizes Available	\$ 20					
Wedge 20x12x1.5 WSEDP2012-BS	CODE	D	В	Width	Insert	Insert		
Scribe Screw End Stop	SS-M5x12 M4x9HD	SEDP-3002030-1¼ or 40	300	1¼ or 40	20	20x30x2 FT		
Key Key	T15 FLAG 4A/F-TEE	SEDR-3002012-1¼ or 40	300	1¼ or 40	20	20x12x1.5	14x14x2	

Last digits on code number denotes bore size choose either $1\!\frac{1}{4}$ or 40.



